



Guide rail 1.1369 Alu in extruded Aluminium

Like the proved 1.1369 guide rail the new guide rail in extruded aluminium 1.1369 Alu can be used in combination with almost every common roller door profile. It guarantees optimal running characteristics, even for roller door shutters with storm hooks.

Corresponding to the inlay profile for guide rail 1.1369, an overhang is already integrated into the shape, which offers additional protection against pulling out the storm hooks in the case of high wind loads.

The inset PVC sealing strip reduces wear and improves smooth running.

All PVC sealing strips are also available with a sealing brush; the grey PVC strip can also be provided with an integrated sealing lip (see fig.).

In addition, reinforcement brackets suitable for protection of the guide rails against deformation under high wind loads are available.

- **measures**
77 x 78,60 x 77 mm
 - **material**
extruded aluminium
 - **weight**
Aluminium 2,34 kg/m
 - **standard length**
6000 mm
 - **combinations**
- | PVC colours | opening width | fitting profiles |
|-------------------------|---------------|---|
| grey / grey | 27 mm | 1.100 D, ISO-SL, 1.100 R, Iso-Plus, 1.95 R, TH80, TH100, 1.1560 |
| anthracite / anthracite | 27 mm | 1.1460 |
| grey / green | 24 mm | 1.1620, 1.1630 |
| green / green | 21 mm | 1.1440 |
| green /brown | 18 mm | 1.1540 |

Due to the tolerances of PVC strips minor deviations of measures are possible.