



fig. with PVC strip grey
with optional sealing lip

Guide rail 1.1369

One for (almost) all.

The 1.1369 guide rail can be used in combination with almost every common roller door profile. It guarantees optimal running characteristics, even for roller door shutters with storm hooks.

For use with wide roller shutters or increased wind loads, an inlay profile can be installed in the guide rail, which offers additional protection against pulling out the storm hooks under load.

The inset PVC sealing strip reduces wear and improves smooth running.

All PVC sealing strips are also available with a sealing brush; the grey PVC strip can also be provided with an integrated sealing lip (see fig.).

In addition, reinforcement brackets suitable for protection of the guide rails against deformation under high wind loads are available.

- **measures**
80 x 78 x 80 mm
- **material**
3.0 mm galvanized steel
- **weight**
steel 5.8 kg/m
- **standard lengths**
3600 mm, 4200 mm, 4800 mm, 5400 mm, 6000 mm, 6600 mm
- **spacing of hole**
600 mm
- **combinations**

PVC colours	opening width	fitting profiles
grey / grey	27 mm	1.100 D, ISO-SL, 1.100 R, Iso-Plus, 1.95 R, TH80, TH100, 1.1560
anthracite / anthracite	27 mm	1.1460
grey / green	24 mm	1.1620, 1.1630
green / green	21 mm	1.1440
green /brown	18 mm	1.1540

Due to the tolerances of PVC strips minor deviations of measures are possible.