



fig. with PVC strip grey with optional sealing brush

Guide rail 1.1371/80

The versatile

The 1.1371 guide rail can be combined with most double and single wall roller door profiles and is suitable for applications where storm hooks are not required. It guarantees optimal running characteristics.

All PVC sealing strips are also available with a sealing brush; the grey PVC strip can also be provided with an integrated sealing lip (see fig.).

In addition, reinforcement brackets suitable for protection of the guide rails against deformation under high wind loads are available.

• **similar articles** (without holes)

article	measures	material
1.1371/50	50 x 52 x 50 mm	galvanised steel*
1.1371/115	115 x 52 x 115 mm	galvanised steel*
1.1371/80	80 x 54 x 80 mm	stainless steel*
1.1372	80 x 54 x 80 mm	aluminium**

in standard lengths of:
* 6000 mm
** 4000 mm, 6000 mm

- **measures**
80 x 52 x 80 mm
- **material**
galvanised steel
- **weight**
~ 4.7 kg/m
- **standard length**
3500 mm, 4000 mm, 4500 mm, 5000 mm, 6000 mm
- **spacing of hole**
700 mm
- **combination**

PVC colour	opening width	fitting profiles
grey / grey	27 mm	1.100 D, ISO-SL, 1.100 R, Iso-Plus, 1.D06, 1.95 R, 1.1460, 1.1560
grey / green	24 mm	1.1620, 1.1630
green / green	21 mm	1.1440
green / brown	18 mm	1.1540

Due to the tolerances of PVC strips minor deviations of measures (opening width) are possible.