



Roller door profile 1.1560

clear lines,
large cut-outs.

ferdinand
braselmann.de

Vielfalt mit Profil

Roller door profile 1.1560



A profile for single-walled roller shutter doors, which as a result of the covering width of 100 mm and its smooth appearance resembles the tried-and-tested 1.100 D roller door profile.

Thanks to its large cut-outs, it achieves light permeability of 42% as a window and grid profile, and is a popular choice for protecting objects such as shop window facades due to good transparency and protection.

• material thickness [mm]

	1.00	1.25	1.50
steel, galvanized	•	• ^P	•
steel, powder colour coated	•	• ^P	•
aluminium, bright	•	• ^P	•
aluminium, powder colour coated	•	• ^P	•
aluminium, plastic colour coated	•	•	
aluminium, anodized 3μ	•	•	•
aluminium, anodized 20μ	•	•	•
stainless steel	•	•	

^P = perforated plate available

• technical details

slats on 1 m height: 10
thickness of slats: ~ 19 mm

• weight (at 1,00 mm)

aluminium: ~ 0.47 kg/m (4.7 kg/m²)
steel: ~ 1.37 kg/m (13.7 kg/m²)

• maximum door width (wind class 2, without storm hooks)

	1.00	1.25	1.5
steel, stainless steel	7000	7600	8200
aluminium	5200	5600	6100

• calculated bale diameter [mm]

opening height	tube diameter [mm]						
	159	169	194	219	267	324	368
3 m	330	330	340	360	400	440	470
3.50 m	360	360	360	390	420	460	470
4 m	360	360	380	400	420	460	470
4.50 m	380	380	390	420	430	480	510
5 m	380	400	400	420	450	500	510
6 m	420	440	430	460	490	520	530
7 m	460	460	470	570	510	540	550
8 m	460	480	510	500	520	540	570